















COMPETITIVE COMPARISON

Feature	Macromatic ARP Series 	Diversified Electronics ARA & ABA Series 	Time Mark 261 Series 	SSAC ARP Series 	MPE 008 Series 
Output Configurations	SPDT DPDT Cross-Wired * DPDT	SPDT DPDT Cross-Wired * DPDT	SPDT DPDT Cross-Wired DPDT	SPDT DPDT Cross-Wired DPDT	SPDT DPDT Cross-Wired * DPDT
Optional Top-Mounted Switch to Lock Loads	Low-Profile Slider Switch	High-Profile Toggle Switch	High-Profile Toggle Switch	Low-Profile 3-Position Rotary Switch	High-Profile Toggle Switch
Input Voltages	12, 24 & 120V AC/DC, 240V AC	24V AC, 120V AC/DC, 208 & 240V AC	12, 24, 120 & 240V AC/DC	24, 120 & 230V AC	120V AC only
Size	1.7" Wide x 2.4" Deep x 3.1" Tall	1.7" Wide x 2.4" Deep x 3.6" Tall	1.95" Wide x 1.95" Deep x 4.0" Tall	1.78" Wide x 2.4" Deep x 3.2" Tall	1.7" Wide x 2.4" Deep x 3.35" Tall
Output Contact Ratings	10A @ 240V AC/30V DC 1/2hp @ 120/240V AC (N.O.)	10A @ 240V AC 1/4hp @ 240V AC 1/8hp @ 120V AC	10A 120V AC	10A @ 240V AC/28V DC 1/3 hp @ 120/240VAC	10A 120V AC
LEDs	2	2	2	2	2
Agency Approvals					
UL Listed with Socket		No	No	No	No
CE Certified		No	No		No
RoHS & RoHS Compliant		No	No	Yes	No
Optional Flange Mounted Version	Yes	No	No	No	No

* Offer versions with input voltage connected to pins 3 & 6 and pins 5 & 6.

MACROMATIC ADVANTAGES

- UL Listed with appropriate socket
- Low-profile selector switch prevents accidental change of status
- AC & DC input voltages (12, 24 & 120V)
- Five year warranty
- Optional Flange-Mounted version for inner-door mounting